



2022 CFORCE 1000 **OVERLAND**

Starting at \$16,299*



12V outlet

Available colour



Free More than \$8,681 in free add-ons!

The most equipped vehicles on the market

Standard features and benefits

Removable rear cargo box Storage capacity of 105L \$1685 value

Skid plate assembly \$1055 value

3,500 Lbs winch (complete assy) \$1055 value

High strength aluminum winch armor \$106 value

Hand guard assembly with windshield \$253 value

14" Beadlock aluminum wheels \$1470 value

Safety and convenience package

Including:

- Del lights
- Lateral mirrors
- Hand protectors
- Trailer connector
- Retaining bars for passenger
- Anti-theft (gear lever lock)
- Double usb plug
- 12v outlet
- Flashers
- Horn

\$612 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km

Specifications

Lateral

Motor

Electric-power

Type: v-twin cylinder, 8-valves, 4 strokes

Displacement: 963 cc

Engine management: Fuel injected engine

Maximum toroue: 58 lbs/pi

Maximum power output: 74 hp

Cooling system: liquid

Starting: electric

Battery: 30 amp

Size / weight

Lenght x width x height: 2310 × 1264 × 1420 mm (90.9 × 49.7 × 56 in)

Seat height: 585 mm

Wheelbase: 1480 mm (58.2 in)

Ground clearance: 300 mm (11 in)

Fuel tank capacity: 30 L (7.9 Gal)

Weight with all fluids: 490 kg (1080 lbs)

Towing capacity: 396 kg (873 lbs) Front/rear rack capacity: 20 kg (44 lbs) / 40 kg (88 lbs)

Brakes

Front and rear brake disc system

Wheels

Front wheels:

cast aluminium alloy $(14 \times 7 \text{ in})$

Rear wheels:

cast aluminium alloy (14 × 8 in)

Front tires: at 27 × 9-14 (stag cote 6 plis)

Fuel injected

Cvtech clutch system

Rear tires: at 27 × 11-14 (stag cote 6 plis)

Transmission

Cv-tech ibc clutch system: variable transmission

Gearbox: 1/h/n/r/p (parking lock shift system)

Power train: 2 wheels / 4 wheels drive, electric locking differential

Suspension and direction

Front suspension: double arm independent suspension, hydraulic shock absorber, five adjustments spring preloads

Front travel: 170 mm (6.7 in)

Rear suspension: double arm independent suspension, hydraulic shock absorber, five adjustments spring preloads

Rear travel: 190 mm (7.4 in)

Steering: electric power steering



