

MIXING BUSINESS WITH PLEASURE

IS YOUR
DRIVING
FORCE.



2022 UFORCE 1000 EPS LX 3 UP

Available colours



Starting at \$17,999*



Free
More than \$6,000 in free add-ons!

The most equipped vehicles on the market

Standard features and benefits

Hitch receiver
\$153 value

Doors
\$1000 value

Roof
\$459 value

5-year CFMOTO warranty
\$3 300 value

3,500 Lbs winch
(complete assy)
\$660 value

Safety and convenience package

- Including:
- Lateral mirrors
 - Retaining bars for passenger
 - Trailer connector
 - 12v outlet
 - Flashers
 - Horn
- \$458 value**

BEST
5
YEAR
LIMITED WARRANTY

5 Year limited warranty:
1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km



Electric-power steering



Lateral mirrors



12V outlet



Cvtech clutch system

Specifications

Motor

Type : v-twin cylinder, 4-stroke, 8- valve
Displacement: 963 cc
Engine management: Fuel injected engine
Maximum torque: 60 lbs/pi
Maximum power output: 79 hp
Cooling system: liquid
Starting: electric
Battery: 30 amp

Size / weight

Length x width x height:
2,945 x 1,615 x 1,850 mm
(116 x 63.5 x 72.8 in)
Seat height: 500 mm
Wheelbase: 2,049 mm (80.7 in)
Ground clearance: 280 mm (11 in)
Fuel tank capacity: 39.25 L (10.5 Gal)
Weight with all fluids:
689,4 kg (1 520 lbs)
Towing capacity: 907 kg (2000 lbs)
Rear box capacity:
453,5 kg (1000 lbs)

Brakes

Front and rear brake disc system

Wheels

Front wheels:
aluminium alloy (14 x 7 in)
Rear wheels:
aluminium alloy (14 x 8 in)
Front tires: at 27 x 9-14
(stag 6 ply rating)
Rear tires: at 27 x 11-14
(stag 6 ply rating)

Transmission

Cv-tech ibc clutch system:
variable transmission
Gear box: l / h / n / r / p
(parking lock shift system)
Power train: 2 wheels / 4 wheels
drive, electric locking differential

Suspension and direction

Front suspension: double arm
independent suspension, hydraulic
shock absorber, five adjustments
spring preloads
Front travel: 230 mm (9.1 in)
Rear suspension: double arm
independent suspension, hydraulic
shock absorber, five adjustments
spring preloads
Rear travel: 230 mm (9.1 in)
Steering: electric power steering
(eps)

Follow us



cfmoto.ca

*The price indicated does not include registration, transport, preparation fees, the cost of accessories and the installation thereof. Applicable taxes not included. Photo is for illustrative purposes only and any accessories shown are not included. Specifications to change without notice. Details in store.